


RECOMMEND PCB LAYOUT
DEFAULT TDL:±0.05



PIN NO.	A	B	C
10	4.00	3.74	1.60
24	6.80	6.54	4.40
30	8.00	7.74	5.60
40	10.00	9.74	7.60
50	12.00	11.74	9.60
60	14.00	13.74	11.60

- NOTES:
1. MATERIAL:
HOUSING: HIGH-TEMP PLASTIC UL 94V-0;
CONTACT: COPPER ALLOY;
PEG: COPPER ALLOY;
 2. PLATING:
CONTACT: GOLD OR TIN PLATED
ON NICKEL OVERALL.
PEG: TIN PLATED ON NICKEL OVERALL.
 3. RATING:
CURRENT RATING: 0.3A AC/DC
VOLTAGE RATING: 50V AC/DC
TEMPERATURE RANGE: -25~+85D;

UNITS: mm

GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:		ELECTRONICS CO., LTD	
X. ° ±5°	0.X±0.25			BTB 0.4MM XP MALE H=0.9MM		5&K	
X.1±2°	0.XX±0.2	APPD:		DWG NO.		SCALE	
XX. ±1°	0.XXX±0.1	CHKD: Skilla		BTB		1:1	
		DR: Kitty				SHEET	
						1 OF 1	
						REV	
						A	