



PIN NO.	A	B	C
10	4.40	3.00	1.60
24	7.20	5.80	4.40
30	8.40	7.00	5.60
40	10.40	9.00	7.60
50	12.40	11.00	9.60
60	14.40	13.00	11.60

RECOMMEND PCB LAYOUT
DEFAULT TOL:±0.05

- NOTES:
1. MATERIAL:
HOUSING: HIGHT-TEMP PLASTIC UL 94V-0;
CONTACT: COPPER ALLOY;
PEG: COPPER ALLOY;
 2. PLATING:
CONTACT: GOLD OR TIN PLATED
ON NICKEL OVERALL.
PEG: TIN PLATED ON NICKEL OVERALL.
 3. RATING:
CURRENT RATING: 0.3A AC/DC
VOLTAGE RATING: 50V AC/DC
TEMPERATURE RANGE: -25~+85DJ;

UNITS: mm		PART NO. (INTENDED USE)		TITLE:	
GENERAL TOLERANCE				BTB 0.4MM XP FEMALE H=0.9MM	
X. ±5°	0. X±0.25	APPD:		DWG NO. BTB	
X. 1±2°	0. XX±0.2	CHKD: Skilla		SCALE SHEET	
XX. ±1°	0. XXX±0.1	DR: Kitty		1:1 1 OF 1	
				REV	
				A	

5&K
ELECTRONICS CO.,LTD



1 2 3 4 5 6 7 8